

DriveCore Install

	AoIP Protocol			HiQnet Ethernet	DSP	Channels			Watts Per Channel*				Low-Z / High-Z**	AUX Port	2x2 GPIO
	None	BLU link	Dante			2	4	8	300W	600W	1,250W	2,400W			
Analog	DCi 2 300	●				●			●				●	●	
	DCi 2 600	●				●				●			●	●	
	DCi 2 1250	●				●					●		●	●	
	DCi 4 300	●					●		●				●	●	
	DCi 4 600	●					●			●			●	●	
	DCi 4 1250	●					●				●		●	●	
	DCi 8 300	●							●	●			●	●	
	DCi 8 600	●							●	●			●	●	
Network	DCi 2 300N		●		●	●			●				●	●	●
	DCi 2 600N		●		●	●				●			●	●	●
	DCi 2 1250N		●		●	●					●		●	●	●
	DCi 2 2400N		●		●	●						●	●	●	●
	DCi 4 300N		●		●	●		●					●	●	●
	DCi 4 600N		●		●	●			●				●	●	●
	DCi 4 1250N		●		●	●					●		●	●	●
	DCi 4 2400N		●		●	●						●	●	●	●
	DCi 8 300N		●		●	●			●				●	●	●
	DCi 8 600N		●		●	●				●			●	●	●
Dante	DCi 4 300DA			●	●		●		●				●	●	●
	DCi 4 600DA			●	●		●			●			●	●	●
	DCi 4 1250DA			●	●		●				●		●	●	●
	DCi 8 300DA			●	●			●	●				●	●	●
	DCi 8 600DA			●	●			●	●				●	●	●

* Measured @ 4Ω; Continuous; All channels driven; 20Hz–20KHz; Minimum guaranteed power

** Low-Z / High-Z configurable per individual channel; 70V / 100V configurable globally